



Borealis Advance
SAE 5W-20; 5W-30 & 10W-30 Synthetic
Blend Motor Oil; API SP, ILSAC GF-6A

Product Description

Borealis Advance SAE 5W-20, 5W-30, and 10W-30 are premium synthetic blend motor oils manufactured for use in modern gasoline engines which require ILSAC GF-6A, API SP, API SN Plus, or API SN performance.

These oils are formulated with a blend of synthetic and group II paraffinic base oils with a premium performance additive package which is specially formulated to protect high compression gasoline direct injection engines delivering superior oxidative stability, deposit control, low speed pre-ignition mitigation and timing chain wear protection.

Typical Properties*

SAE J300 Viscosity Grade	5W-20	5W-30	10W-30
Appearance, Visual	Amber, Transparent, Liquid		
Viscosity @ 40°C, cSt, ASTM D445	48.95	62.8	70.7
Viscosity @ 100°C, cSt, ASTM D445	8.3	10.8	10.9
Viscosity Index, ASTM D2270	145	165	145
CCS Apparent Viscosity, cP, ASTM D5293	5,300@-30°C	5,800@-30°C	5,000@-25°C
MRV Apparent Viscosity, cP, ASTM D4684	18,000@-35°C	22,000@-35°C	15,000@-30°C
Flash Point, °C, ASTM D92	210	210	215
Pour Point, °C, ASTM D97	-43	-42	-40

*The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.

Exceeds Performance Requirements

API SP with ResourceConserving, API SN Plus, API SN

ILSAC GF-6A, GF-5

Chrysler MS6395

Ford WSS-M2C945-B1(5W-20); Ford WSS-M2C946-B1(5W-30)

Product Code

SAE 5W-20- SXP010; SAE 5W-30- SXP011; SAE 10W-30- SXP012

