



Borealis Maximum
SAE 5W-20, 5W-30 & 10W-30 Synthetic
Blend Motor Oil; API SN, ILSAC GF-5

Product Description

Borealis Maximum Synthetic Blend Motor Oils, SAE 5W-20, 5W-30, and 10W-30, API SN, ILSAC GF-5 are formulated with a blend of conventional and synthetic base oils and a premium additive package. These oils are designed for use in carbureted, fuel injected, turbocharged gasoline engines. These oils exceed the performance requirements of API SN and ILSAC GF-5.

Typical Properties*

SAE J300 Viscosity Grade	5W-20	5W-30	10W-30
Appearance, Visual	Amber, Transparent, Liquid		
Viscosity @ 40°C, cSt, ASTM D445	47.75	61.25	68.75
Viscosity @ 100°C, cSt, ASTM D445	8.3	10.8	10.9
Viscosity Index, ASTM D2270	150	170	150
CCS Apparent Viscosity, cP, ASTM D5293	4,800@-30°C	5,200@-30°C	4,900@-25°C
MRV Apparent Viscosity, cP, ASTM D4684	15,000@-35°C	18,000@-35°C	9,000@-30°C
Flash Point, °C, ASTM D92	215	215	218
Pour Point, °C, ASTM D97	-44	-42	-40

*The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.

Exceeds Performance Requirements

API SN, API SM, API SL, API SJ
ILSAC GF-5
Chrysler MS6395
GM6094M
Ford WSS-M2C946-A (5W-30); Ford WSS-M2C945-A (5W-20)

Product Code

SAE 5W-20 – SXT104
SAE 5W-30 – SXT105
SAE 10W-30 – SXT106

