



Borealis Heavy Duty
Synthetic Blend Heavy-Duty Engine Oils
SAE 25W-60; API CH-4/SL

Product Description

Borealis Synthetic Blend Heavy-Duty Engine Oil, SAE 25W-60, API CH-4/SL is a parasyntetic crankcase lubricant for use in modern diesel engines. Formulated with a blend of synthetic and conventional base oils as well as a premium quality additive package, this oil exhibits good detergent, dispersant, anti-wear, anti-corrosion, anti-oxidant, and anti-foaming properties.

Typical Properties*

SAE J300 Viscosity Grade

25W-60

Appearance, Visual	Dark Green
Viscosity @ 40°C, cSt, ASTM D445	252.15
Viscosity @ 100°C, cSt, ASTM D445	24.0
Viscosity Index, ASTM D2270	120
CCS Apparent Viscosity, cP, ASTM D5293	6,800@-10°C
Flash Point, °C, ASTM D92	235
Pour Point, °C, ASTM D97	-20
Total Base Number, mg KOH/g, ASTM D2896	9

*The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.

Exceeds Performance Requirements:

API CH-4, CF-4, CF-2, CF
API SL, SJ, SG, SF

Product Code

SAE 25W-60 – SFX212

