



Borealis Maximum HD Motor Oil
SSAE30,SAE40&SAE50 API
SN/CF

Product Description

Borealis Maximum SAE 30, SAE 40, SAE 50 HD Motor Oils API SN/CF is a gasoline and light-duty diesel engine oil blended with group II paraffinic base stocks and a premium additive package. These oils exhibit good anti-wear, anti-oxidant, anti-foaming, detergent, and dispersant characteristics. This oil exceeds the performance requirements of API SN/CF.

Typical Properties*

SAE J300 Viscosity Grade	SAE 30	SAE 40	SAE 50
Appearance, Visual	Amber, Transparent, Liquid		
Viscosity @ 40°C, cSt, ASTM D445	86.35	130.50	181.05
Viscosity @ 100°C, cSt, ASTM D445	10.5	14.0	17.5
Viscosity Index, ASTM D2270	105	105	105
Flash Point, °C, ASTM D92	215	220	225
Pour Point, °C, ASTM D97	-15	-15	-5

*The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.

Exceeds Performance Requirements

API SN/CF

Product Code

SAE 30 – SXT109
SAE 40 – SXT110
SAE 50 – SXT111

