



Borealis Advance Elite
SAE 0W-20, 5W-20, 5W-30 & 10W-30 Full
Synthetic Motor Oil, API SP, ILSAC GF-6A

Product Description

Borealis Advance Elite SAE 0W-20, 5W-20, 5W-30, and 10W-30 are premium full synthetic motor oils manufactured for use in modern gasoline engines which require ILSAC GF-6A, API SP, API SN Plus, or API SN performance.

These oils are formulated with synthetic base oils and a premium performance additive package which is specially formulated to protect high compression gasoline direct injection engines delivering superior oxidative stability, deposit control, low speed pre-ignition mitigation and timing chain wear protection.

Typical Properties*

<i>SAE J300 Viscosity Grade</i>	<i>0W-20</i>	<i>5W-20</i>	<i>5W-30</i>	<i>10W-30</i>
Appearance, Visual	Amber, Transparent, Liquid			
Viscosity @ 40°C, cSt, ASTM D445	44.55	47.75	61.25	68.75
Viscosity @ 100°C, cSt, ASTM D445	8.3	8.3	10.8	10.9
Viscosity Index, ASTM D2270	165	150	170	150
CCS Apparent Viscosity, cP, ASTM D5293	5,400@-35°C	4,800@-30°C	5,200@-30°C	4,900@-25°C
MRV Apparent Viscosity, cP, ASTM D4684	22,000@-40°C	15,000@-35°C	18,000@-35°C	9,000@-30°C
Flash Point, °C, ASTM D92	210	215	215	218
Pour Point, °C, ASTM D97	-47	-44	-42	-40

*The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.

Exceeds Performance Requirements

API SP with Resource Conserving, API SN Plus, API SN ILSAC GF-6A, GF-5

GM dexos1™ Gen 2

Chrysler MS6395

Ford WSS-M2C947-B1 (0W-20); Ford WSS-M2C945-B1 (5W-20); Ford WSS-M2C946-B1 (5W-30)

Product Code

SAE 0W-20 – SPE002; SAE 5W-20 – SPE003; SAE 5W-30 – SPE004; SAE 10W-30 – SPE005

